

# CHF464DGT-GAS



**Forno a gas combinato convezione vapore 4 teglie 600 x 400 mm con pannello digitale touch con tecnologia BLACK MASK**

**Gas combi oven 4 trays 600 x 400 mm with digital touch panel with BLACK MASK technology**



## Plus

Sistema carter d'aria brevettato **Airflowlogic™**  
Sistema vapore diretto brevettato **Humulogic™**

Software per gestione dell'umidità

Accensione forno programmabile

N° 40 ricette memorizzate

Sistema per HACCP

Cerniere porta regolabili

Regolamento 2016/426/UE

## Dotazione di serie

**Imballo cartone+pallet (LxPxH mm)** 908 x 1088 x 866 mm

**Supporti laterali** 1dx + 1sx

**Cavo** Monofase [3G 1,5]-L=1600 mm

**Presenza USB**

**Predisposizione sonda al cuore**

**Predisposizione lavaggio automatico**

**Vaschetta raccogli condensa con scarico su porta**

**Cerniera con bloccoporta per aperture regolate a 60°, 90°, 120°, 180°**

**Ugello GPL**

## Dimensioni

**Dimensioni (LxPxH mm)** 850 x 1035 x 801

**Peso (kg)** 102

**Passo guide (mm)** 80

## Caratteristiche elettriche

**Portata termica (kW)** 9,3

**Frequenza (Hz)** 50/60

**Voltaggio (V)** AC 220/230

**N° motori** 1 bidirezionale

**Generatore di vapore (kW)** /

**Protezione acqua** IPX3

## Caratteristiche funzionali

**Alimentazione** Multigas (collaudo a metano)

**Capacità** N° 4 teglie/griglie 600 x 400 mm

**Cottura** Semistatica + ventilata

**Vapore** Diretta con regolazione automatica attraverso selettore touch (10 steps)

**Camera di cottura** Acciaio AISI 304

**Temperatura** 30 - 260 °C

**Controllo temperatura** Sonda digitale

**Pannello comandi** Black mask electronic control

**N° programmi** 100

**Fasi programmabili** 10

**Temperatura preimpostata** 180 °C

**Preriscaldamento** Disponibile  
Apertura laterale dx

**Porta** Ventilata

**Piedini** Vetro ispezionabile  
Regolabili



## Plus

Patented fan guard system **Airflowlogic™**  
Patented system for direct steam **Humulogic™**

Humidity management software

Programmable oven start

N° 40 recipes stored

HACCP system

Adjustable door hinges

Regulation 2016/426/UE

## Equipment

**Cardboard box dimensions with pallet (WxDxH mm)** 908 x 1088 x 866 mm

**Lateral supports** 1 right + 1 left

**Cable** Single-phase [3G 1,5]-L=1600 mm

**USB port**

**Core probe predisposition**

**Automatic washing system predisposition**

**Condensate collection bowl, with drain on door**

**Hinge with door locking for openings adjusted at 60°, 90°, 120°, 180°**

**Nozzle for LPG**

## Dimensional features

**Dimensions (WxDxH mm)** 850 x 1035 x 801

**Weight (kg)** 102

**Distance between rack rails (mm)** 80

## Electrical features

**Thermal supply (kW)** 9,3

**Frequency (Hz)** 50/60

**Voltage (V)** AC 220/230

**N° motors** 1 bidirectional

**Boiler (kW)** /

**Protection against water** IPX3

## Functional features

**Power** Multigas (tested for natural gas)

**Capacity** N° 4 trays/grids 600 x 400 mm

**Type of cooking** Semistatic + ventilated

**Steam** Direct steam controlled by touch screen (10 levels)

**Cooking chamber** AISI 304 stainless steel

**Temperature** 30 - 260 °C

**Temperature control** Digital probe thermometer

**Control panel** Black mask electronic control

**N° programs** 100

**Programmable cooking steps** 10

**Pre-heating temperature** 180 °C

**Pre-heating function** Programmable  
Right side opening

**Door** Ventilated

**Feet** Inspectionable glass  
Adjustable