# CHF 1111 TOP




















## Gas combi oven 7 trays 1/1 GN with touch screen


Its performance makes it the ideal ally of every gastronomy professional. The new 11tray Millennial gas oven guarantees optimal results in a short amount of time. Captivating design, technology and performance at the highest levels, a capacity of 11 GN1/1 trays.

A loyal ally for medium/large restaurants that can handle even the most complex recipes with maximum simplicity. 500 programmable recipes, 42 languages, up to 24 h delayed cooking programs, and 5 ventilation speed settings are just some of the features that characterize all the Millennial line.









#### **Dimensional features**

Dimensions (WxDxH mm)	730 x 850 x 1230
Weight (kg)	152
Distance between rack rails (mm)	68

#### **Electrical features**

Liectifical features	
Thermal supply (kW)	18
Frequency (Hz)	50/60
Voltage (V)	AC 220/230
N° motors	2 bidirectional
Boiler (kW)	/
Protection against water	IPX3

Functional features	
Power	Multigas (tested for natural gas)
Capacity	N° 11 trays/grids 1/1 GN
Type of cooking	Semistatic + ventilated
Steam	Direct steam controlled by touch screen (10 levels)
Cooking chamber	AISI 304 stainless steel
Temperature	30 - 260 °C
Temperature control	Digital probe thermometer
Control panel	Touch screen
N° programs	500
Programmable cooking steps	10
Pre-heating temperature	180 °C
Pre-heating function	Programmable
Door	Right side opening Ventilated Inspectionable glass
Feet	Adjustable

### **Equipment**

Cardboard box dimensions with pallet (WxDxH mm)	790 x 905 x 1300 mm	
Lateral supports	1dx + 1sx	
Cable	Single-Phase [3G 1,5]-L=1600 mm	
USB port		
Multipoint core probe cod. MKSCMU		
Support for core probe cod. MKSSC	/A	
Automatic washing system integrated		
Condensate collection bowl, with drain on door		
Hinge with door locking for openings adjusted at 60°, 90°, 120°, 180°		
Nozzle for LPG		

#### Plus

Adjustable door hinges Regulation 2016/426/UE

Patented fan guard system <b>Airflowlogic</b>	гм
Patented system for direct steam <b>Humilo</b>	gic™
Patented system for cooking chamber dry	ying <b>Drylogic™</b>
Available on request at the order	Left side opening door
Humidity management software	
Wi-Fi communication system	
Knob for quick selection of the touch scre	een
Programmable oven start	
N ° 40 recipes stored	
Control panel in 42 languages: Arabic, Armenian, Azerbaijani, Bahasa (Indonesia Bulgarian, Chinese, Croatian, Czech, Danish, Dut French, Georgian, German, Greek, Hungarian, Ic Latvian, Lithuanian, Norwegian, Persian (Iran), PR Romanian, Russian, Serbian, Slovenian, South Ko Turkish, Ukrainian, Vietnamese	tch, English, Estonian, Finnish, elandic, Italian, Japanese, Kazakh, hilippine, Polish, Portuguese,
HACCP system	