# **CHF 511 TOP GAS**





















## Gas combi oven 5 trays 1/1 GN with touch screen

 $5\ \mbox{GN1/1}$  trays with a new touch screen interface: high performance to obtain the best results in the kitchen with excellent, even cooking and fast times with consequent reduction in energy consumption. The new Millennial oven allows complete management of the features. An oven that can be connected to the internet through a Wi-Fi connection to update the firmware, cookbooks, and technical documentation and manuals in the oven. Millennial, the perfect oven to always stay connected!









## **Dimensional features**

Dimensions (WxDxH mm)	730 x 850 x 800
Weight (kg)	89
Distance between rack rails (mm)	68
Electrical features	
Thermal supply (kW)	9
Frequency (Hz)	50/60
Voltage (V)	AC 220/230
N° motors	1 bidirectional
Boiler (kW)	/

Protection against water

Feet

<b>Functional features</b>	
Power	Multigas (tested for natural gas)
Capacity	N° 5 trays/grids 1/1 GN
Type of cooking	Semistatic + ventilated
Steam	Direct steam controlled by touch screen (10 levels)
Cooking chamber	AISI 304 stainless steel
Temperature	30 - 260 ℃
Temperature control	Digital probe thermometer
Control panel	Touch screen
N° programs	500
Programmable cooking steps	10
Pre-heating temperature	180 ℃
Pre-heating function	Programmable
Door	Right side opening Ventilated Inspectionable glass

## **Equipment**

Cardboard box dimensions with pallet (WxDxH mm)	790 x 905 x 870 mm
Lateral supports	1dx + 1sx
Cable	Single-Phase [3G 1,5]-L=1600 mm
USB port	
Multipoint core probe cod. MKSCMU	
Support for core probe cod. MKSSC/A	
Automatic washing system integrated	
Condensate collection bowl, with drain of	on door
Hinge with door locking for openings ad	ljusted at 60°, 90°, 120°, 180°
Nozzle for LPG	

HACCP system Adjustable door hinges

Regulation 2016/426/UE

IPX3

Adjustable

Plus	
Patented fan guard system <b>Airflowlogic™</b>	
Patented system for direct steam <b>Humilo</b>	gic™
Patented system for cooking chamber dry	⁄ing <b>Drylogic™</b>
Available on request at the order	Left side opening door
Humidity management software	
Wi-Fi communication system	
Knob for quick selection of the touch scre	en
Programmable oven start	
N ° 40 recipes stored	
Control panel in 42 languages: Arabic, Armenian, Azerbaijani, Bahasa (Indonesia Bulgarian, Chinese, Croatian, Czech, Danish, Dut French, Georgian, German, Greek, Hungarian, Ice Latvian, Lithuanian, Norwegian, Persian (Iran), Ph Romanian, Russian, Serbian, Slovenian, South Ko Turkish, Ukrainian, Vietnamese	ch, English, Estonian, Finnish, elandic, Italian, Japanese, Kazakh, nilippine, Polish, Portuguese,