CHF 623 TOP COMPACT



















Electric COMPACT combi oven with touch screen 6 trays 2/3 GN

Although it is just 50 cm wide, it encloses all the potential to achieve optimal cooking uniformity. A compact, fast, intuitive and simple oven. Designed for restaurants and delicatessens, which must combine all the technology of a cutting-edge product with limited kitchen space. Like all those in the Millennial range, the oven has IPX5 water protection rating. The oven also offers the multi-point core probe and integrated automatic wash as standard. Maximum efficiency in minimum space.





Dimensional features

Dimensions (WxDxH mm)	500 x 750 x 700
Weight (kg)	61,6
Distance between rack rails (mm)	68
Electrical features	

Power supply (kW)	5,2
Frequency (Hz)	50/60
Voltage (V)	AC 380/400 3N
N° motors	1 bidirectional
Boiler (kW)	/
Protection against water	IPX5

Functional features	
Power	Electricity
Capacity	N° 6 trays/grids 2/3 GN
Type of cooking	Semistatic + ventilated
Steam	Direct steam controlled by touch screen (10 levels)
Cooking chamber	AISI 304 stainless steel
Temperature	30 - 270 °C
Temperature control	Digital probe thermometer
Control panel	Touch screen
N° programs	500
Programmable cooking steps	10
Pre-heating temperature	180 °C
Pre-heating function	Programmable
Door	Right side opening Ventilated Inspectionable glass
Modularity	
Feet	Adjustable

Equipment

Cardboard box dimensions with pallet (WxDxH mm)	570 x 800 x 870 mm
Lateral supports	1 right + 1 left
Cable	Three-phase+neutral [5G 1,5]-L=1600 mm
USB port	
Multipoint core probe cod. MKSCMU	
Automatic washing system integrated	
Condensate collection bowl, with drain on	door
Hinge with door locking for openings adju	ısted at 60°, 90°, 120°, 180°
Support for core probe MKSSC/A	

Turkish, Ukrainian, Vietnamese

Adjustable door hinges

HACCP system

Plus		
Patented fan guard system Airflowlogic™		
Patented system for direct steam I	Humilogic™	
Patented system for cooking char	nber drying Drylogic™	
	Voltage (V) : AC 220/230 3	
Available on request at the order	Voltage (V) : AC 220/230	
	Left side opening door	
Humidity management software		
Wi-Fi communication system		
Knob for quick selection of the to	uch screen	
Programmable oven start		
N ° 40 recipes stored		
Control panel in 42 languages: Arabic, Armenian, Azerbaijani, Bahasa (Bulgarian, Chinese, Croatian, Czech, Da French, Georgian, German, Greek, Hun Latvian, Lithuanian, Norwegian, Persian Romanian, Russian, Serbian, Slovenian,	nish, Dutch, English, Estonian, Finnish, garian, Icelandic, Italian, Japanese, Kazakh, n (Iran), Philippine, Polish, Portuguese,	