## **CHF711MCN-GAS**



Right side opening

Ventilated Inspectionable glass

Adjustable

## Gas combi oven 7 trays 1/1 GN with electromechanic panel













Plus		
Available on request at the order	Left side opening o	door *
Adjustable door hinges		
Regulation 2016/426/UE		
	* addition of 300 € on the pri	ice list
Equipment		
Cardboard box dimensions with pallet (Wx	<b>DxH mm)</b> 788 x 903 x 101	6 mm
Lateral supports	1 right +	- 1 left
Cable	Single-phase [3G 1,5]-L=160	0 mm
Manual washing predisposition		
Condensate collection bowl, with drain	n on door	
Hinge with door locking for openings	adjusted at 60°, 90°, 120°, 180°	
Nozzle for LPG		
Dimensional features		
Dimensions (WxDxH mm)	730 x 855	x 951
Weight (kg)		108,5
Distance between rack rails (mm)		68
Electrical features		
Thermal supply (kW)		13,5
Frequency (Hz)	50 (60 on der	mand)
Voltage (V)	AC 22	0/230
N° motors	2 bidirect	ionals
Boiler (kW)		/
Protection against water		IPX3
Functional features		
Power	Multigas (tested for natur	
Capacity	N° 7 trays/grids 1	
Type of cooking	Vent	tilated
Steam	Direct	steam
Steam	controlled by kr	10b (5
Cooking chamber	AISI 304 stainles	e neepes)
Temperature	100 - 2	260°C
Temperature control	Thern	nostat
Control panel	Electromechanic - righ	nt side
N° programs		/
Programmable cooking steps		/
Dro hosting tomporature		

Pre-heating temperature Pre-heating function

Door

Feet